

HTML

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Link Locker</title>
<link rel="stylesheet" href="Link Locker.css">
</head>
<body>
  <a href="https://www.youtube.com/@EBExplain" target="_blank">
    <button id="button1" onclick="unlockButton()">Subscribe Channel to Watch
Video</button>
  </a>
  
<p>Link Locked</p>
  <button id="button2" onclick="navigateToLink()">Watch Video</button>
</body>
</html>
```

CSS

```
body {
  font-family: Arial, sans-serif;
  margin: 0;
  padding: 0;
  display: flex;
  flex-direction: column;
  justify-content: center;
  align-items: center;
  height: 100vh;
  background: linear-gradient(180deg, #1c88cf, rgb(226, 207, 207), #ad1c1c);
  color: white;
}

button {
  padding: 12px 25px;
  margin: 10px;
  border: none;
  border-radius: 25px;
  background: linear-gradient(90deg, #df5252, #1c88cf);
  color: white;
  font-size: 18px;
  font-weight: bold;
  cursor: pointer;
  transition: all 0.3s ease;
  box-shadow: 0 4px 6px rgba(0, 0, 0, 0.2);
}

button:hover {
  transform: scale(1.1);
  background: linear-gradient(90deg, #1c88cf, #df5252);
  box-shadow: 0 6px 10px rgba(0, 0, 0, 0.3);
}

#button2 {
  display: none; /* Initially hiding the second button */
  animation: fadeIn 1s ease-out;
}

img {
  border-radius: 15px;
}

@keyframes fadeIn {
  from {
```

```
    opacity: 0;
    transform: translateY(20px);
}
to {
    opacity: 1;
    transform: translateY(0);
}
}
```

Script

```
<script>
    function unlockButton() {
        var button2 = document.getElementById('button2');
        button2.style.display = 'inline'; // Display the second button
    }

    function navigateToLink() {
        window.location.href = 'https://ancientartz.site'; // Change this to the desired
link
    }
</script>
```